

ARTICLE 2: FALSIFICATION: Any person who knowingly makes any false statements, representation or certification in any application, record, report, plan or other document filed or required to be maintained pursuant to this Chapter or Wastewater Discharge Permit, or who falsifies, tampers with, or knowingly renders inaccurate any monitoring device or method required under this Chapter, shall be subject to the penalties and costs provided in Part 6 and shall in addition be guilty of a misdemeanor and upon conviction, be punished by a fine of one hundred dollars (\$100.00) to five hundred dollars (\$500.00).

7-1-2: BUILDING SEWERS AND CONNECTIONS:

- (A) No unauthorized person shall uncover or make any connection with, or opening into, any public sewer without obtaining a written permit from the Superintendent.
- (B) The sewer permits shall distinguish between residential, commercial and industrial users. The permit application shall be supplemented by any plans and specifications, or other information considered pertinent in the judgment of the Superintendent.
- (C) Permit fees shall be:
 - 1. One hundred dollars (\$100.00) for residential connection and an additional ten dollars (\$10.00) per unit for all units in excess of one (1);
 - 2. One hundred dollars (\$100.00) for commercial and industrial connections.Payable on issuance of the permit by the Village.
- (D) All costs incidental to the installation of the building sewer shall be paid by the applicant. The applicant shall indemnify the Village from any loss or damage that may result from the installation with the minimum fee being five hundred dollars (\$500.00) deposit for repair of the adjacent street.
- (E) A separate and independent building sewer shall be provided for every building. Any pre-existing connections that serve two (2) or more buildings shall be separated and made separate and distinct sewer connections within one (1) year from the enactment of this Section.

- (F) Old building sewers may be used in connection with new buildings after approval by the Superintendent.
- (G) Building sewer shall be:
1. Cast iron soil pipe, ASTM Specification A-74 as revised, or
 2. Vitrified clay sewer pipe, ASTM Specification C-13 or C-200 as revised, or
 3. Other suitable material allowed by the National Plumbing Code, except bituminized fiber pipe, but including PVC.
- (H) Joints shall be tight and waterproof.
- (I) Any part of the building sewer that is located within ten feet (10') of a water service pipe shall be constructed of cast iron soil pipe with lead joints. Cast iron pipe may be specified by the Superintendent when adjacent to tree roots.
- (J) The size and slope of the sewer shall be subject to the approval of the Superintendent, but shall not be less than four inches (4") in diameter, and with a slope on one-eighth inch (1/8") per foot.
- (K) The building sewer shall be brought to the building at an elevation below the basement floor, except on approval of the Superintendent, overhead plumbing may be provided.
- (L) The building sewer must be:
1. More than three feet (3') from any bearing wall.
 2. More than three feet (3') deep.
 3. Uniform in alignment except changes in direction may be allowed if centered on a suitable cleanout.
- (M) Excavation work shall be:
1. Open trench work with proper shoring unless otherwise approved by the Superintendent.

2. In compliance with ASTM Specification C 12-58-T for pipe laying and backfill, except no backfill shall be placed until the work has been inspected.
- (N) The connections of building sewers into the public sewer shall conform to the aforesaid requirements or to the standards of Water Pollution Control Federation Manual of Practice 29, whichever standard is more severe. Any deviation from the described procedures and materials must be approved by the Superintendent.

7-1-3: AUTHORITY OF ADMINISTRATIVE PERSONNEL:

ARTICLE 1: INSPECTION: The Superintendent with proper identification shall be permitted to enter onto all properties for the purposes of inspection, observation, measurement, sampling and testing pertinent to the discharge to the public system. The Superintendent may require additional samples or require a sampling control manhole in order to facilitate the sampling process.

ARTICLE 2: INDUSTRIAL PROCESSES: The Superintendent is authorized to obtain information concerning industrial processes which have a direct bearing on the kind and source of discharge. The Superintendent shall require plans and specifications for said private waste system prior to issuing a permit.

ARTICLE 3: EASEMENTS: The Superintendent, with proper identification, shall be permitted to enter all private properties through which the Village holds an easement. Under the terms of pre-existing conditions, should the Village discover sewer lines lying under private property without duly negotiated easements, the Village may authorize the Superintendent to enter upon and conduct such activities as necessary to maintain the collection system. The Village hereby assumes any contingent liability for damage to private property as may result from said actions as determined by the actual status of the physical condition of the surface land.

ARTICLE 4: PROTECTION OF SEWER SYSTEM: Pursuant to its authority to make, enact and enforce ordinances for improvement, care and protection of the Village and its waste treatment system, and of its public water supply outside the Village, and of standards for control of